



United States Patent
Stolzenthaler, III

Alerting method for a wireless communication device

Abstract (as currently amended)

An alerting method which will amplify and broadcast the notification signal produced by a wireless communication device, or use a notification signal produced by the device invention. The ~~invention~~ device will signal an incoming message or a missed message by amplification of the audio or visual signal generated by the wireless communication apparatus, or audio or visual signals generated by the device invention itself. The ~~invention~~ device may also charge the power source contained in the wireless apparatus and/or power the wireless ~~apparatus~~ communication device. The device may also serve as a microphone and speaker attachment to the wireless communication device apparatus communication.

Inventor: **Stolzenthaler, III; Stanford C.** (5911 Willow Glen Dr., Baton Rouge, LA 70809)

Assignee: **Stolzenthaler, III; Stanford C.** (Baton Rouge, LA)

Appl. No:

Filed:

Current U.S. Class:

Intern'l Class:

Field of Search:

Claims (as currently amended)

What is claimed is:

1. A device to notify of messages to a wireless communication device by amplification of the notification signal of the wireless communication device, comprising of a audio signal, visual signal, or a display screen, comprising:
 - an alerting device;
 - a microphone to capture the audio notification signal of the wireless communication device and also the voice of the user;
 - a speaker for producing an alerting sound or message from the wireless communication device;
 - a light to indicate a message is captured by the wireless communication device;
 - the ~~invention~~ device will attach to the wireless communication device by means of plug, pin or wire, contact connection, optical connection or low-power signal connection or ~~other methods~~ radio wave or a combination of any methods;
 - the volume and frequency of the audio signal produced by the ~~invention~~ device may be adjustable;
 - the attachment system between the wireless communication device and the ~~invention~~ device can be unique to each brand and/or model of wireless communication device;
 - a display.
2. The device of claim #1 may further be comprised of a power source to charge the internal battery of the wireless communication device or power the wireless communication device or ~~invention~~ the device. An interface to which the wireless communication device is attached, comprising:
 - a light to indicate attachment of the wireless communication device to the alerting device;
 - a light to indicate the ~~invention~~ device has power;

the ~~invention~~ device can be powered by AC current, DC current, or battery;

a power connection on the ~~invention~~ device for connection with an outside power source;

a transformer in ~~invention~~ the device for reduction said outside power source to provide the appropriate current to power or charge the wireless communication device;

a system to terminate charging of the batteries of the wireless communication device when said device is fully charged if the wireless communication device has batteries;

a self contained power source for the ~~invention~~ device which can power the ~~invention~~ device when it is not connected to an external power source

Description

BACKGROUD OF THE INVENTION DEVICE

1. Field of the Invention

The present ~~invention~~ device relates to a wireless communication device such as a wireless phone, portable computer, handle held or portable wireless communication device, and in particular, to an alerting method and apparatus for alerting a user by sound, light or display to signal a message arrival to the wireless communication device.

Mobil wireless communication devices use various methods to produce a signal of incoming message. Some may produce a sound signal, vibrate or use visual means to notify the user. As the wireless communication devices have achieved widespread use, and have become important for many as their primary communication method of communication. Therefore the importance of being aware of incoming messages from their mobile wireless communication devices has increased and the production a signal which will notify the user who is not in close proximity to the wireless communication device is necessary.

SUMMARY OF THE ~~INVENTION~~ DEVICE

The present ~~invention~~ device is to provide an alerting method for a wireless communication device which will generate a notification by audio or visual signal, which can be heard or seen from greater distance or for a longer time than the alerting signal generated by the wireless communication device.

Another objective of the present ~~invention~~ device is to provide power to both recharge the internal power supply of the wireless communication device and also power the wireless communication device while it is attached to the ~~invention~~ device. The ~~invention~~ device will either be powered by an external power supply such as AC or DC current or by internal battery. The ~~invention~~ device will alter these power sources to the proper voltage and amperage need by the attached wireless communication device.

The ~~invention~~ device will receive the incoming message signal from the wireless communication device by one of the following methods: (a) A microphone attached to the ~~invention~~ device will receive the signal from the wireless communication device for the ~~invention~~ device; or (b) the wireless communication device can be directly attached to the ~~invention~~ device by a plug, pin wire, contact connection, optical connection, or non-contact low-power signal connection or ~~other method~~ radio wave to make a "attachment" to the ~~invention~~ device, or any other type of contact between the ~~communication device and the invention~~.

The ~~invention~~ device will be signaled by the wireless communication device when a message is incoming. This signal will be amplified by the ~~invention~~ device and then broadcast by the ~~invention~~ device by the method or methods chosen by the user either audio, visual or both. The signal generated by the ~~invention~~ device may be the same as the wireless communication device, or a different signal produced by the ~~invention~~ device. The ~~invention~~ device may also repeat the broadcast of the signal, at a predetermined rate, after the wireless communication device has ceased its signal.

The ~~invention~~ device will have a signal light which will alert of a message. This light either may stay on or flash until the message of the wireless communication device has been answered.

The invention device may also have a display which will either display information generated by the wireless communication device, or a message generated by the invention device.

The invention device will contain a switch to terminate the audio and/or visual signal of the invention device.

The invention device will have a signal light to indicate the wireless communication device is properly attached to the invention device.

The invention device will signal by light when the wireless communication device is being charged by the invention and also when the wireless communication device is full charged and the charging has ceased.

BRIEF DESCRIPTION OF THE DRAWING (as currently amended)

With reference now the drawing of a new method of indication of incoming message on a mobile wireless communication device. More specifically, referring to FIG. 1, it will be noted that the first embodiment of the invention device includes a housing 20. A connection 13 to an outside power source such as AC or DC current connects to a transformer 14 which will power both the invention device and charge the wireless communication device. A battery 10 may also be attached to the transformer device to power either the invention device or wireless communication device. The battery may be either disposable or rechargeable. A controller 16 will stop charging the wireless communication device when its power source is fully charged. A light 15 will indicate when the invention device has power. A light 4 will signal when the wireless communication device is properly attached to the invention device and is being powered by the invention device or charging its power source. A light 5 will indicate the wireless communication device is charging. The wireless communication device will be docked 11 to the invention device to transfer a signal to indicate an incoming message to the invention device. The wireless communication device will also be attached 12 to the invention device to transfer power to the wireless communication device. A microphone 7 may also be attached to the invention device this shall be used to receive an audio signal generated from the wireless communication device if the wireless communication

device is not able to connect to the invention device to transfer a signal indicating a message. The signal from the microphone or the signal directly from the wireless communication device will go to amplifier 17 which will transmit a signal to the speaker 1. This microphone may also be used to transfer audio signals to the wireless communication device. The invention device may use any or all of the following methods to indicate an incoming message. The speaker 1 will transmit an audio alert produced by the synthesizer 21 or be used to amplify the audio of the wireless communication device. The speaker volume will be regulated by a controller 3 on the device invention. A device to produce a ringer tone 9 will be connected to a timer 8 which will be used to control the repetition of the signal which was selected to indicate a message present. A display 2 can be used to indicate a message is present and will produce a visual signal generated from the invention device by the audio, video, graphic control unit 18, if the visual signal from the wireless communication device is not selected. A signal light 6 will also be used to indicated a message was received by the wireless communication device. An on/off switch 19 will be on the invention device to power the device invention on or off.

With respect to the above description then, it is to realized that the optimum dimensional relationships for the parts of the invention device, to include variations in size, materials, shape, form, function and manner of operation, assembly and use, are deemed readily apparent and obvious to one skilled in the art, and all equivalent relationships to those illustrated in the drawings and described in the specification are intended to be encompassed by the present invention device. Therefore, the foregoing is considered as illustrative only of the principles of the invention device. Given the speed at which semiconductor , electronics and software technology is progressing, the preceding is a description of the preferred embodiment of my inventive system which I contemplate will be implemented with the most technical and cost effective technology available at the time it is used for a particular application. Further, since numerous modifications and changes will readily occur to those skilled in the art, it is not desired to limit the invention device to the exact construction and operation shown and described, and accordingly, all suitable modifications and equivalents may be resorted to

falling within the scope of the ~~invention device~~.
